

LATEX	YELLOW	FLOCK-LINED	S-XL	RE-USABLE	MULTI-PURPOSE
-------	--------	-------------	------	-----------	---------------

Latex glove with flocked interior. Recommended for use in cleaning and hygiene, suitable for multiple purposes.

**Characteristics**

<b>Not suitable for latex allergic people.</b>	<b>Grip improving texture on palms and fingers</b>
<b>Latex comfort</b>	<b>Flexible and adaptable</b>
<b>Flock-lined for easy use</b>	<b>Soft</b>

**Packaging**

- 144 pairs per carton
- Individually packed
- Carton contains: 12 packs of 12 units
- Dimension of pack: 250 x 140 x 10 mm



**Labelling** Manufacturing date, expiration date, batch number, reference and EAN code. Product name in several languages: Spanish, English, French, German, Italian, Portuguese, Russian, Ukrainian, Turkish, Hungarian.

CE marking, protection pictograms, safety standards and legislation. Size, size guide and units.

#### Standards:

- CE marking PPE Category III according to Regulation (EU) 2016/425
- EN ISO 374-1:2016 (Type C)
- EN ISO 374-5:2016 Protection against micro-organisms (bacteria and fungi)
- EN 420:2003+A1:2009
- EN 388:2006. Protection against mechanical risks (abrasion, blade cuts, tears, punctures, sharp cuts)

#### Chemical resistance:

##### PERMEATION (EN ISO 374-1:2016/A1.2018, type C)

Gloves are classified in terms of time of passage, according to each individual chemical for which the glove resists permeation:

CHEMICALS	LEVEL	LETTER
SODIUM HYDROXIDE 40%	2	K

#### Performance Level:

Time (min)	> 10	> 30	> 60	> 120	> 240	> 480
Performance Level	1	2	3	4	5	6

#### DEGRADATION

Degradation % (DR) is determined for each chemical used in the permeation tests.

- (DR) K: SODIUM HYDROXIDE 40%      1.3%

The “VLX” glove PPE should be used to protect the user’s hand against chemical risks (products and levels mentioned above) and against microbiological risks.

The present PPE should never be used against other risks than those described above. The use of his PPE should be evaluated correctly depending on the place of work.

EN 388: 2016

EN ISO 374-1:2016 / Type C

EN ISO 374-5:2016



1000X



K



GLOVE SIZES		S	M	L	XL
Length	Min mm	295	295	295	295
Palm thickness	±0,02 mm	0.30	0.30	0.30	0.30

